

Another product proudly supplied to you by the partnership of



# SUNSHADOW CA Series (Screen Hybrid)

## 3 % Openness

Composition: 35% Polyester / 65% PVC  
 Width: 2500mm  
 Weight: 320gsm ± 5%  
 Thickness: 0.45mm ± 5%  
 Tensile Strength Warp150 / Weft 120 daN/5cm  
 Tearing Strength Warp 4.5 / Weft 6.9 daN  
 Colourfastness: Grade 8 (ISO 105 B02, Xenarc lamp)  
 Assembly: Ultrasonic, Knife, Crush or Pressure Cut  
 Roll Size: 30 Lineal Metres  
 Care Label: Screen - Sunscreen

### Fire Retardant Results

AS 1530.3-1999		AWTA Test Report Number 7-571230-BQ		Date: 23/02/10
Ignitability (Range 0-20)	Spread of Flame (Range 0 – 10)	Heat Evolved (Range 0 – 10)	Smoke Developed (Range 0 – 10)	
<b>0</b>	<b>0</b>	<b>0</b>	<b>5</b>	



**Please note:** Variations in colour may occur from one production batch to another. Exact colour match to sample cannot be guaranteed. If an exact match is required a sample must be submitted at the time of placing your order.

© Copyright 2011 The Bricos Goup Pty Ltd ABN 99 001 808 966

# CA Series (Screen Hybrid)

